

Tyre Size	PR	Tread design					Rim Fitment (1)		Tube	Tyre Dimensions max in service (2)		Inflation Pressure (+/-15%) [ bar ]	Load capacity (3)			
		SD SKS CLASSIC	SD SKS XTRA	TRACTION-MASTER R1	HA SKS	HA SKZ	Rec	Alternative		(+/-2%)			8 km/h [ kg ]	16 km/h [ kg ]	Creep (4) [ kg ]	Static [ kg ]
										Width [ mm ]	O.D [ mm ]					
5.70-12	6	■	■		■◆		4.50I	5JA	TBLS	157	585	4.20	660	520	760	1040
23x8.5-12	4	□	■				7.00I	7JA	TBLS	231	589	2.25	640	510	740	1010
	6	■	■		■	3.50						825	650	950	1300	
	10	■	□		■	5.90						1110	880	1280	1750	
	12	■	□		■	7.00						1235	980	1420	1950	
26x12-12	8	■		□		10.50	8.50/8.50 JA	TBLS	307	648	3.50	1370	1080	1580	2160	
	10	■		□	□						4.50	1630	1290	1870	2580	
27x10-12	14	■				8.00G		TT	275	704	7.00	3545	3215	4080	4115	
7.00-15	6	■				5.50	6 LB	TBLS	223	808	4.10	1440	1140	1660	2280	
27x8.5-15	6	■	□		■	7JA	6.5 K/7J	TBLS	231	695	3.50	1030	810	1180	1630	
	8	■	■		■						4.10	1110	880	1280	1750	
27x10.5-15	8	■			■	8.50	8 LB	TBLS	259	695	4.10	1160	920	1330	1830	
31x15.5-15	8	■		□	■	13.00	13 LB	TBLS	391	788	3.10	1690	1340	1940	2670	
	10				■						4.10	1985	1570	2280	3140	
	12				■						5.25	2230	1760	2560	3520	
26x12-16.5(300/40-16.5)	10			□		9.75		TBLS	307	648	4.00	1630	1290	1870	2580	
10-16.5(30)	8				■	8.25		TBLS	285	760	4.20	1875	1480	2160	2960	
	10				□						5.25	2140	1690	2460	3380	
	12				■						6.30	2405	1900	2770	3800	
10-16.5	6	■	■			8.25		TBLS	285	788	3.15	1590	1260	1830	2510	
	8	■	■		■						4.20	1875	1480	2160	2960	
	10	■	■		■						5.25	2140	1690	2460	3380	
	12	■	■		■						6.30	2405	1900	2770	3800	
31.5x13-16.5	10				■	9.75			353	800	4.90	2435	1920	2800	3850	
12-16.5	8	■	■		■	9.75		TBLS	332	848	3.50	2180	1720	2510	3440	
	10	■	■		■						4.50	2545	2010	2930	4020	
	12	■	■		■						5.60	2880	2280	3310	4550	
33x15.5-16.5	12				■	12.00		TBLS	424	838	4.10	2900	2290	3340	4580	
	14				■						4.90	3150	2490	3620	4980	
	16				■						5.60	3875	3060	4460	6120	
14-17.5	10	■	■		■	10.5		TBLS	388	954	3.85	3105	2450	3570	4910	
	12	■	■		■						4.80	3550	2800	4080	5610	
	14				■						5.60	3875	3060	4460	6120	
380/65-19.5(14.5-19.5)	12				□	11.75	12.25	TBLS	431	991	4.20	4170	3290	4800	6590	
	14				■◆						5.60	5070	4010	5830	8010	
	16				■◆						7.00	6000	4740	6900	9480	
	8				□						2.80	3255	2570	3740	5140	
15-19.5	10				■	11.75	12.25	TBLS	431	1056	3.50	3745	2960	4310	5920	
	12				■						4.20	4170	3290	4800	6590	
	14				■						5.60	5070	4010	5830	8010	
	16				■						7.00	6000	4740	6900	9480	
	16				■						7.00	7040	5560	8100	11120	
	20				■						9.00	8325	6580	9570	13150	

Also available in All White and Electrically Conducting	
■	Available
□	Available later 2002
■◆	On request only

- REMARKS (1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre / rim combination particularly with regard to rim profile, wheel strength and maximum inflation pressure.
- (2) The sizes given are according to ETRTO or TRA, where available. For exact sizes, please consult the technical department.
- (3) For skid-steer and mini-loader service.
- (4) Creep speed is a travel rate of not over 60 m in a 30 minute period.



SD SKS Classic    SD SKS XTRA    TRACTION-MASTER R1    HA SKS    HA SKZ Lifemaster

COMPANY QUALITY SYSTEMS APPROVED ACCORDING TO



ISO 9001 - 1994 No: 98186



ISO 9002 - 1994 No: I 60002

