

TRELLEBORG

T - 8 0 0



PNEUMATIC TIRES



The Trelleborg pneumatic tire range has been developed for heavy duty use on forklift trucks and other industrial vehicles. This line of tires offer customers an additional range of tires besides solid rubber and polyurethane products. All the tires have a lug type tread pattern which provides optimal grip and traction in every condition. The cross-ply or diagonal structure further insures high stability and maximum safety. The casing is of high tensile strength nylon cord which offers good resistance to fatigue and improves comfort.

- **NATURAL RUBBER**
- **GOOD RESISTANCE TO FATIGUE**
- **HIGH STABILITY MAXIMUM SAFETY**
- **OPTIMAL GRIP AND TRACTION**



TRELLEBORG T-800

- **TRELLEBORG ENGINEERED**
- **PREMIUM COMPOUNDS**
- **HIGH RELIABILITY**
- **FOR USE IN INDUSTRIAL APPLICATIONS**
- **AVAILABLE IN POPULAR SIZES**
- **COST EFFECTIVE**



T-800

Size	P.R.	Recommended rim	Profile T-800	Loadcapacity forklift up to 25 km/h (kg)		Inflation pressure (±15%)		Inflated dimensions (mm)		Weight Tire (kg)
				Front	Rear	PSI	Bar	Width	O.D.	
5.00-8	10	3.00	*	1415	1090	145	10.00	134	465	6.2
18x7-8	16	4.33	*	2145	1650	145	10.00	160	453	9.5
6.00-9	12	4.00	*	1885	1450	145	10.00	155	540	9.7
21x8-9	14	6.00	*	2535	1950	130	9.00	198	546	14.0
6.50-10	10	5.00	*	1950	1500	112	7.75	183	597	11.1
23x9-10	20	6.50	*	3445	2650	145	10.00	228	585	22.1
7.00-12	14	5.00	*	2755	2120	131	9.00	196	685	16.0
27x10-12	14	8.00	*	3545	2725	102	7.00	245	691	28.9
7.00-15	14	5.50	*	3310	2545	134	9.25	190	755	21.2
7.50-15	14	6.00	*	3640	2800	134	9.25	216	805	24.5
28x9-15 (8.15-15)	14	7.00	*	3900	3000	145	10.00	217	722	23.7
8.25-15	14	6.50	*	4225	3250	116	8.00	255	834	30.5
250-15	20	7.50	*	5135	3950	145	10.00	240	760	36.7
300-15	20	8.00	*	6275	4825	135	9.30	290	840	44.7

1) The above load capacities are based on available E.T.R.T.O and T.R.A. specifications for load and steering wheels on counterbalanced forklift trucks.

2) The Trelleborg pneumatic tires are available as complete sets (tire/tube/flap) or as tire & flap only.