

Kenda K610 Kinetics

- premium pneumatic forklift truck tyre



The range of Kenda K610 tyres, has been specifically designed to provide a premium product of excellent durability and longevity. Fork lift trucks are required to work long hours with total reliability, especially in the modern industrial environment where 'just in time' delivery has become commonplace.

The high tensile steel beads are complimented by tough reinforcement to ensure minimum wear and tear where the tyres run on the wheel rim. The sidewalls are strongly supported by multiple layers of reinforcement, combined with a tough scuff guard of a specially formulated rubber compound, greatly increasing the resistance to sidewall impacts. The heavy-duty tread design has been created specifically to give reduced noise levels, and precise steering with minimum stress. The centre area of the tread has a high net to gross contact area, giving excellent steering stability and precision combined with long life and excellent traction. The shoulder areas of the tread, with lower net to gross contact area and flexible block structure, also enhances the ease of steering by reducing the steering forces. This gives the benefit of reduced stresses within the tyre and the vehicle. The tread area is further braced by an extra carcass belt, which gives improved and even footprint pressure and increased resistance to penetrations.

The K610 is a very tough, reliable tyre giving excellent value for money.



Tyres - Forklift Truck

Kenda K610 Kinetics



Dimension	PR/LI	Tread pattern	TL/TT	Sales unit	57 07562+	mm	mm	kg	kg	kg	km/h	bar	
8"													
5.00-8	10PR	Kenda K610 Kinetics	TT	Tyre TT	270357	468	140	1090	1415	1090	25	10.00	3.00
18x7-8	16PR	Kenda K610 Kinetics	TT	Tyre TT	270463	462	168	1650	2145	1650	25	10.00	4.33
9"													
6.00-9	12PR	Kenda K610 Kinetics	TT	Tyre TT	270364	543	160	1450	1885	1450	25	10.00	4.00
10"													
6.50-10	12PR	Kenda K610 Kinetics	TT	Tyre TT	270371	590	182	1650	2145	1650	25	9.00	5.00
23x9-10	20PR	Kenda K610 Kinetics	TT	Tyre TT	270487	585	230	2650	3445	2650	25	10.00	6.50
12"													
7.00-12	14PR	Kenda K610 Kinetics	TT	Tyre TT	270388	680	191	2120	2755	2120	25	9.00	5.00
	16PR	Kenda K610 Kinetics	TT	Tyre TT	272436	680	191	2240	2910	2240	25	10.00	5.00
23x10-12	20PR	Kenda K610 Kinetics	TT	Tyre TT	272443	600	250	2900	3770	2900	25	10.00	8.00
27x10-12	16PR	Kenda K610 Kinetics	TT	Tyre TT	270494	685	250	3000	3900	3000	25	8.00	8.00
	24PR	Kenda K610 Kinetics	TT	Tyre TT	272450	685	250	3875	5038	3875	25	10.35	8.00
15"													
7.00-15	14PR	Kenda K610 Kinetics	TT	Tyre TT	270395	756	200	2520	3275	2520	25	8.80	5.5
7.50-15	16PR	Kenda K610 Kinetics	TT	Tyre TT	270401	785	215	3000	3900	3000	25	10.00	6.00
8.15-15	14PR	Kenda K610 Kinetics	TT	Tyre TT	270418	710	230	3000	3900	3000	25	10.00	7.00
8.25-15	14PR	Kenda K610 Kinetics	TT	Tyre TT	270425	841	247	3250	4225	3250	25	8.00	6.5
250-15	20PR	Kenda K610 Kinetics	TT	Tyre TT	270432	742	240	3875	5040	3875	25	10.00	7.50
300-15	20PR	Kenda K610 Kinetics	TT	Tyre TT	270449	840	290	5000	6500	5000	25	9.00	8.00
16"													
7.50-16	12PR	Kenda K610 Kinetics	TT	Tyre TT	272467	805	215	2790	3630	2790	25	8.00	6.00
20"													
9.00-20	14PR	Kenda K610 Kinetics	TT	Tyre TT	272474	1015	265	4500	5850	4500	25	9.00	7.00
10.00-20	16PR	Kenda K610 Kinetics	TT	Tyre TT	272481	1080	294	5000	6500	5000	25	9.00	7.5
11.00-20	18PR	Kenda K610 Kinetics	TT	Tyre TT	272498	1110	305	6000	7800	6000	25	10.00	8.00
12.00-20	20PR	Kenda K610 Kinetics	TT	Tyre TT	272504	1145	325	6900	8970	6900	25	10.00	8.5
	24PR	Kenda K610 Kinetics	TT	Tyre TT	272511	1145	325	7470	9710	7470	25	10.30	8.5
24"													
12.00-24	20PR	Kenda K610 Kinetics	TT	Tyre TT	272528	1245	320	7500	9750	7500	25	10.00	8.5
	24PR	Kenda K610 Kinetics	TT	Tyre TT	272535	1245	320	7500	9750	7500	25	10.00	8.5
14.00-24	24PR	Kenda K610 Kinetics	TT	Tyre TT	272542	1360	380	9500	12350	9500	25	10.00	10.00
	28PR	Kenda K610 Kinetics	TT	Tyre TT	272559	1360	380	9690	12595	9690	25	10.35	10.00



Kenda K610 Kinetics